
OpenColorIO Configuration for ACES Documentation

Release 1.0.0

OpenColorIO Contributors

Oct 26, 2022

CONTENTS

1	1.1	Features	3
2	1.2	User Guide	5
2.1	User Guide	5
3	1.3	API Reference	11
3.1	API Reference	11
4	1.4	About	53
Index			55

The OpenColorIO Configuration for ACES is an open-source Python package implementing support for the generation of the *OCIO* configurations for the Academy Color Encoding System (ACES).

It is freely available under the [New BSD License](#) terms.

CHAPTER
ONE

1.1 FEATURES

The following features are available:

- Automatic **OCIO Reference** configuration generation for *aces-dev CTL* reference implementation.
 - Discovery of *aces-dev CTL* transforms.
 - Generation of the *CTL* transforms graph.
 - **Spreadsheet**-driven generation.
- Generators producing the **OCIO CG** and **Studio** configurations. - **Spreadsheet**-driven generation.
- Included *CLF* transforms along with generator and discovery support.

1.2 USER GUIDE

2.1 User Guide

The user guide provides an overview of **OpenColorIO Configuration for ACES** and explains important concepts and features, details can be found in the [API Reference](#).

2.1.1 Installation Guide

Cloning the Repository

The *OpenColorIO Configuration for ACES* repository uses [Git submodules](#) thus cloning the repository requires initializing them:

```
git clone --recursive https://github.com/AcademySoftwareFoundation/OpenColorIO-Config-  
→ACES.git
```

If you have already cloned the repository and forgot the *–recursive* argument, it is possible to initialize the submodules as follows:

```
git submodule update --init --recursive
```

Poetry

The *OpenColorIO Configuration for ACES* repository adopts [Poetry](#) to help managing its dependencies, this is the recommended way to get started with development.

Assuming [python >= 3.8](#) is available on your system along with [OpenColorIO >= 2](#), the development dependencies are installed with [Poetry](#) as follows:

```
git clone --recursive https://github.com/AcademySoftwareFoundation/OpenColorIO-Config-  
→ACES.git  
cd OpenColorIO-Config-ACES  
poetry install --extras "optional"
```

The *aces-dev CTL* reference graph can be plotted but it requires [Graphviz](#) to be installed on the system and having installed the optional [pygraphviz](#): python package:

```
poetry install --extras "optional graphviz"
```

Docker

Installing the dependencies for the [previous config generator](#) was not a trivial task. For ease of use an `aswf-docker` based container is now available.

Creating the container from the [Dockerfile](#) is done as follows:

```
docker build -t aswf/opencolorio-config-aces:latest .
```

or alternatively, if the dependencies described in the next section are satisfied:

```
invoke docker build
```

Then, to run `bash` in the container:

```
docker run -it -v ${PWD}:/home/aswf/OpenColorIO-Config-ACES aswf/opencolorio-config-  
→aces:latest /bin/bash
```

Pypi

The **OpenColorIO Configuration for ACES** package requires various dependencies in order to run and be able to generate the OCIO configurations:

Primary Dependencies

- `python >= 3.8, < 3.11`
- `black`
- `OpenColorIO`

Optional Dependencies

- `colour`
- `graphviz`
- `jsonpickle`
- `networkx`
- `pygraphviz`

Development Dependencies

- `black`
- `coverage`
- `coveralls`
- `flake8`
- `invoke`
- `mypy`
- `pre-commit`
- `pydata-sphinx-theme`
- `pydocstyle`

- pytest
- pyupgrade
- restructuredtext-lint
- sphinx >= 4, < 5
- twine

Once the dependencies are satisfied, the **OpenColorIO Configuration for ACES** package can be installed from the [Python Package Index](#) by issuing this command in a shell:

```
pip install --user opencolorio-config-aces
```

2.1.2 Usage

Tasks

Various tasks are currently exposed via `invoke`.

This is currently the recommended way to build the configuration until a dedicated CLI is provided.

Listing the tasks is done as follows:

```
invoke --list
```

Reference Config

<i>Task</i>	<i>Command</i>
Build	<i>invoke build-config-reference</i>
Build (Docker)	<i>invoke docker-run-build-config-reference</i>
Updating Mapping File	<i>invoke update-mapping-file-reference</i>

CG Config

<i>Task</i>	<i>Command</i>
Build	<i>invoke build-config-cg</i>
Build (Docker)	<i>invoke docker-run-build-config-cg</i>
Updating Mapping File	<i>invoke update-mapping-file-cg</i>

Studio Config

<i>Task</i>	<i>Command</i>
Build	<i>invoke build-config-studio</i>
Build (Docker)	<i>invoke docker-run-build-config-studio</i>
Updating Mapping File	<i>invoke update-mapping-file-studio</i>

2.1.3 Process

aces-dev Discovery & Classification

The config generation process starts with a set of definitions and classes to discover, parse and classify the CTL transforms from [aces-dev](#):

- `opencolorio_config_aces.discover_aces_ctl_transforms()`
- `opencolorio_config_aces.classify_aces_ctl_transforms()`
- `opencolorio_config_aces.print_aces_taxonomy()`

Note: This approach allowed us to improve the consistency of the **CTL** transforms ACESTransformID while fixing various filename issues.

Using ACES2065-1 and OCES as connection spaces, it is possible to build a colour conversion graph with all the high-level relevant transforms.

- `opencolorio_config_aces.build_aces_conversion_graph()`
- `opencolorio_config_aces.plot_aces_conversion_graph()`

Analytical & Reference Configs Generation

The colour conversion graph is then used to create the *Analytical* config that maps 1-to-1 the [aces-dev](#) **CTL** transforms to theoretical **OpenColorIO** builtin transforms. This config does not work but it is useful to test basic generation capabilities whilst diagnosing issues in the mapping.

The *Reference* config is driven by a CSV file generated from a [spreadsheet](#) mapping the ACESTransformID to **OpenColorIO** builtin transforms.

- `opencolorio_config_aces.generate_config_aces()`

CLF Transforms Generation, Discovery & Classification

The working group decided to express additional colour transforms using **CLF**. Some **CLF** transforms can be serialised into a config which reduces the need for external files. Each **CLF** transform has a CLFtransformID specified according to the [CLF Formatting for ACES OCIO Config](#) document.

The repository contains code to generate, discover and classify the additional **CLF** transforms that the *CG* and *Studio* configs require.

- `opencolorio_config_aces.discover_clf_transforms()`
- `opencolorio_config_aces.classify_clf_transforms()`
- `opencolorio_config_aces.print_clf_taxonomy()`

CG Config Generation

The *CG* config generator also uses a CSV file generated from a [spreadsheet](#) that expresses which ACESTransformID should be used from the *Reference* config and which CLFtransformID should be used from the shipped **CLF** transforms.

- `opencolorio_config_aces.generate_config_cg()`

The conversion process is as follows:

aces-dev Discovery & Classification -> Reference Config Generation -> CLF Transforms Generation, Discovery & Classification -> CG Config Generation

Studio Config Generation

The *Studio* config generator follows the same approach but uses a different [pivot table](#) of the spreadsheet.

- `opencolorio_config_aces.generate_config_studio()`

The conversion process is as follows:

aces-dev Discovery & Classification -> Reference Config Generation -> CLF Transforms Generation, Discovery & Classification -> Studio Config Generation

1.3 API REFERENCE

3.1 API Reference

3.1.1 OpenColorIO Configuration for ACES

Common LUT Format Discovery

`opencolorio_config_aces`

<code>classify_clf_transforms(...)</code>	Classify given <i>CLF</i> transforms.
<code>discover_clf_transforms([root_directory])</code>	Discover the <i>CLF</i> transform paths in given root directory: The given directory is traversed and the <code>*.clf</code> files are collected.
<code>filter_clf_transforms(clf_transforms[, ...])</code>	Filter given <i>CLF</i> transforms with given filterers.
<code>print_clf_taxonomy()</code>	Print the <i>builtins</i> <i>CLF</i> taxonomy:
<code>unclassify_clf_transforms(...)</code>	Unclassifie given <i>CLF</i> transforms.

`opencolorio_config_aces.classify_clf_transforms`

`opencolorio_config_aces.classify_clf_transforms(unclassified_clf_transforms)`

Classify given *CLF* transforms.

Parameters

`unclassified_clf_transforms` (`dict`) – Unclassified *CLF* transforms as returned by `opencolorio_config_aces.discover_clf_transforms()` definition.

Returns

`{“family”1: {“genus”1: {}CLF1, ..., “family”n: {“genus”2: {}CLF2}}`

where

`{}CLFn = {“basename”n: CLFTransformn, ..., “basename”n+1: CLFTransformn+1}`

Return type

`dict`

Examples

```
>>> clf_transforms = classify_clf_transforms()
...     discover_clf_transforms()
>>> family = sorted(clf_transforms.keys())[0]
>>> str(family)
'arri'
>>> genera = sorted(clf_transforms[family])
>>> print(genera)
['Input']
>>> genus = genera[0]
>>> sorted(clf_transforms[family][genus].items())[:2]
[('ARRI.Input.ARRI_LogC3_Curve_EI800', CLFTransform('arri...input...ARRI.Input.ARRI_
->LogC3_Curve_EI800.clf')), ('ARRI.Input.ARRI_LogC3_EI800_to_ACES2065-1',_
->CLFTransform('arri...input...ARRI.Input.ARRI_LogC3_EI800_to_ACES2065-1.clf'))]
```

opencolorio_config_aces.discover_clf_transforms

```
opencolorio_config_aces.discover_clf_transforms(root_directory='/home/docs/checkouts/readthedocs.org/user_build_
config-aces/envs/stable/lib/python3.9/site-
packages/opencolorio_config_aces/clf/transforms')
```

Discover the *CLF* transform paths in given root directory: The given directory is traversed and the *.clf files are collected.

Parameters

`root_directory` (unicode) – Root directory to traverse to find the *CLF* transforms.

Returns

```
{“directory1” : [“transforma.clf”, “transformb.clf”],
..., 
“directoryn” : [“transformc.clf”, “transformd.clf”]}
```

Return type

dict

Examples

```
>>> clf_transforms = discover_clf_transforms()
>>> key = sorted(clf_transforms.keys())[0]
>>> os.path.basename(key)
'input'
>>> sorted([os.path.basename(path) for path in clf_transforms[key]])[:2]
['ARRI.Input.ARRI_LogC3_Curve_EI800.clf', 'ARRI.Input.ARRI_LogC3_EI800_to_ACES2065-1.
->clf']
```

`opencolorio_config_aces.filter_clf_transforms`

`opencolorio_config_aces.filter_clf_transforms(clf_transforms, filterers=None)`

Filter given *CLF* transforms with given filterers.

Parameters

- `clf_transforms` (dict or list) – *CLF* transforms as returned by `opencolorio_config_aces.classify_clf_transforms()` or `opencolorio_config_aces.unclassify_clf_transforms()` definitions.
- `filterers` (array_like, optional) – List of callables used to filter the *CLF* transforms, each callable takes a *CLF* transform as argument and returns whether to include or exclude the *CLF* transform as a bool.

Returns

$[CLFTransform_1, \dots, CLFTransform_n]$

Return type

list

Warning:

- This definition will forcibly unclassify the given *CLF* transforms and return a flattened list.

Examples

```
>>> clf_transforms = classify_clf_transforms(
...     discover_clf_transforms())
>>> sorted(
...     filter_clf_transforms(
...         clf_transforms,
...         [lambda x: x.family == 'blackmagic'],
...         key=lambda x: x.path)[0]
CLFTransform('blackmagic...input...BlackmagicDesign.Input.BMDFilm_Gen5_Log-Curve.clf
˓→')
```

`opencolorio_config_aces.print_clf_taxonomy`

`opencolorio_config_aces.print_clf_taxonomy()`

Print the *builtins* *CLF* taxonomy:

- The *CLF* transforms are discovered by traversing the directory defined by the `opencolorio_config_aces.clf.reference.ROOT_TRANSFORMS_CLF` attribute using the `opencolorio_config_aces.discover_clf_transforms()` definition.
- The *CLF* transforms are classified by *family* e.g. *aces*, and *genus* e.g. *undefined* using the `opencolorio_config_aces.classify_clf_transforms()` definition.
- The resulting data structure is printed.

opencolorio_config_aces.unclassify_clf_transforms

`opencolorio_config_aces.unclassify_clf_transforms(classified_clf_transforms)`

Unclassifie given *CLF* transforms.

Parameters

`classified_clf_transforms` (`dict`) – Classified *CLF* transforms as returned by `opencolorio_config_aces.classify_clf_transforms()` definition.

Returns

$[CLFTransform_1, \dots, CLFTransform_n]$

Return type

`list`

Examples

```
>>> clf_transforms = classify_clf_transforms(  
...     discover_clf_transforms())  
>>> sorted(  
...     unclassify_clf_transforms(clf_transforms), key=lambda x: x.path)[0]  
CLFTransform('arri...input...ARRI.Input.ARRI_LogC3_Curve_EI800.clf')
```

Common LUT Format Generation**opencolorio_config_aces**

<code>generate_clf_transform(filename, transforms, ...)</code>	Take a list of transforms and some metadata and write a <i>CLF</i> transform file.
--	--

opencolorio_config_aces.generate_clf_transform

`opencolorio_config_aces.generate_clf_transform(filename, transforms, clf_transform_id, name, input_desc, output_desc, aces_transform_id=None, style=None)`

Take a list of transforms and some metadata and write a *CLF* transform file.

Parameters

- `filename` (`str`) – *CLF* filename.
- `transforms` (`list`) – Transforms to generate the *CLF* transform file for.
- `clf_transform_id` (`str`) – *CLFtransformID*.
- `name` (`str`) – *CLF* transform name.
- `input_desc` (`str`) – *CLF* input descriptor.
- `output_desc` (`str`) – *CLF* output descriptor.
- `aces_transform_id` (`str`, optional) – *ACESTransformID*.
- `style` (`str`, optional) – *OpenColorIO* builtin transform style.

Returns

Updated *GroupTransform*.

Return type
ocio.GroupTransform

Ancillary Objects

`opencolorio_config_aces.clf`

<code>generate_clf_transforms_arri(output_directory)</code>	Generate CLF files for ARRI color encodings and save to disk.
<code>generate_clf_transforms_bmdfilm(output_directory)</code>	Make the CLF file for BMD-Film_WideGamut_Gen5 plus matrix/curve CLFs.
<code>generate_clf_transforms_canon(output_directory)</code>	Make the CLF file for Canon C-Log3 Cinema Gamut plus matrix/curve CLFs.
<code>generate_clf_transforms_davinci(output_directory)</code>	Make the CLF file for DaVinci Intermediate Wide Gamut plus matrix/curve CLFs.
<code>generate_clf_transforms_itu(output_directory)</code>	Generate OCIO Utility CLF transforms.
<code>generate_clf_transforms_ocio(output_directory)</code>	Generate OCIO Utility CLF transforms.
<code>generate_clf_transforms_panasonic(...)</code>	Make the CLF file for V-Log - V-Gamut plus matrix/curve CLFs.
<code>generate_clf_transforms_red(output_directory)</code>	Make the CLF file for RED Log3G10 REDWideGamutRGB plus matrix/curve CLFs.
<code>generate_clf_transforms_sony(output_directory)</code>	Make all the Sony CLFs.

`opencolorio_config_aces.clf.generate_clf_transforms_arri`

`opencolorio_config_aces.clf.generate_clf_transforms_arri(output_directory)`

Generate CLF files for ARRI color encodings and save to disk.

Parameters

`output_directory` (PosixPath or WindowsPath) – Directory where generated CLF files should be saved.

Returns

Dictionary of *OpenColorIO Transform* instances.

Return type

`dict`

References

-

`opencolorio_config_aces.clf.generate_clf_transforms_bmdfilm`

`opencolorio_config_aces.clf.generate_clf_transforms_bmdfilm(output_directory)`

Make the CLF file for BMDFilm_WideGamut_Gen5 plus matrix/curve CLFs.

Returns

Dictionary of *CLF* transforms and *OpenColorIO GroupTransform* instances.

Return type

`dict`

References

- Blackmagic Design. (2021). Blackmagic Generation 5 Color Science.

Notes

- The resulting *CLF* transforms were reviewed by *Blackmagic*.

`opencolorio_config_aces.clf.generate_clf_transforms_canon`

`opencolorio_config_aces.clf.generate_clf_transforms_canon(output_directory)`

Make the CLF file for Canon C-Log3 Cinema Gamut plus matrix/curve CLFs.

Returns

Dictionary of *CLF* transforms and *OpenColorIO GroupTransform* instances.

Return type

`dict`

References

- Canon. (2018). White Paper on Canon Log. Retrieved September 22, 2022, from <http://downloads.canon.com/nw/learn/white-papers/cinema-eos/white-paper-canon-log-gamma-curves.pdf>

Notes

- The resulting *CLF* transforms were reviewed by *Canon*.

`opencolorio_config_aces.clf.generate_clf_transforms_davinci`

`opencolorio_config_aces.clf.generate_clf_transforms_davinci(output_directory)`

Make the CLF file for DaVinci Intermediate Wide Gamut plus matrix/curve CLFs.

Returns

Dictionary of *CLF* transforms and *OpenColorIO GroupTransform* instances.

Return type

`dict`

References

- Blackmagic Design. (2020). Wide Gamut Intermediate DaVinci Resolve. Retrieved December 12, 2020, from https://documents.blackmagicdesign.com/InformationNotes/DaVinci_Resolve_17_Wide_Gamut_Intermediate.pdf?v=1607414410000

Notes

- The resulting *CLF* transforms were reviewed by *Blackmagic*.

`opencolorio_config_aces.clf.generate_clf_transforms_itu`

`opencolorio_config_aces.clf.generate_clf_transforms_itu(output_directory)`

Generate OCIO Utility CLF transforms.

`opencolorio_config_aces.clf.generate_clf_transforms_ocio`

`opencolorio_config_aces.clf.generate_clf_transforms_ocio(output_directory)`

Generate OCIO Utility CLF transforms.

`opencolorio_config_aces.clf.generate_clf_transforms_panasonic`

`opencolorio_config_aces.clf.generate_clf_transforms_panasonic(output_directory)`

Make the CLF file for V-Log - V-Gamut plus matrix/curve CLFs.

Returns

Dictionary of *CLF* transforms and *OpenColorIO GroupTransform* instances.

Return type

`dict`

References

- Panasonic. (2014). VARICAM V-Log/V-Gamut (pp. 1–7). http://pro-av.panasonic.net/en/varicam/common/pdf/VARICAM_V-Log_V-Gamut.pdf

Notes

- The resulting *CLF* transforms were reviewed by *Panasonic*.

`opencolorio_config_aces.clf.generate_clf_transforms_red`

`opencolorio_config_aces.clf.generate_clf_transforms_red(output_directory)`

Make the CLF file for RED Log3G10 REDWideGamutRGB plus matrix/curve CLFs.

Returns

Dictionary of *CLF* transforms and *OpenColorIO GroupTransform* instances.

Return type

`dict`

References

- RED Digital Cinema. (2017). White Paper on REDWideGamutRGB and Log3G10. Retrieved January 16, 2021, from <https://www.red.com/download/white-paper-on-redwidegamutrgb-and-log3g10>

Notes

- The resulting *CLF* transforms were reviewed by *RED*.

`opencolorio_config_aces.clf.generate_clf_transforms_sony`

`opencolorio_config_aces.clf.generate_clf_transforms_sony(output_directory)`

Make all the Sony CLFs.

Returns

Dictionary of *CLF* transforms and *OpenColorIO GroupTransform* instances.

Return type

`dict`

Notes

- The full transforms generated here were developed in collaboration with Sony.

Generation

Profile Version

`opencolorio_config_aces`

<code>ProfileVersion([major, minor])</code>	Define the data container for an <i>OpenColorIO</i> config profile version.
<code>PROFILE_VERSION_DEFAULT</code>	Define the data container for an <i>OpenColorIO</i> config profile version.
<code>SUPPORTED_PROFILE VERSIONS</code>	Built-in mutable sequence.

`opencolorio_config_aces.ProfileVersion`

`class opencolorio_config_aces.ProfileVersion(major=None, minor=None)`

Define the data container for an *OpenColorIO* config profile version.

Parameters

- `major` (`int`, optional) – Major version number.
- `minor` (`int`, optional) – Minor version number.

`major`

`minor`

Examples

```
>>> profile_version = ProfileVersion()
>>> profile_version.parse("2.0")
>>> profile_version.major
2
>>> profile_version.minor
0
>>> profile_version_1 = PROFILE_VERSION_DEFAULT
>>> profile_version_2 = ProfileVersion(2, 1)
>>> profile_version_2 > profile_version_1
True
```

`__init__(major=None, minor=None)`

Methods

`__init__([major, minor])`

`parse(vstring)`

Attributes

<code>major</code>	Getter property for the major version number.
<code>minor</code>	Getter property for the minor version number.
<code>version_re</code>	

`opencolorio_config_aces.PROFILE_VERSION_DEFAULT`

`opencolorio_config_aces.PROFILE_VERSION_DEFAULT = ProfileVersion ('2.0')`

Define the data container for an *OpenColorIO* config profile version.

Parameters

- `major` (`int`, optional) – Major version number.
- `minor` (`int`, optional) – Minor version number.

`opencolorio_config_aces.major`

`opencolorio_config_aces.minor`

Examples

```
>>> profile_version = ProfileVersion()
>>> profile_version.parse("2.0")
>>> profile_version.major
2
>>> profile_version.minor
0
>>> profile_version_1 = PROFILE_VERSION_DEFAULT
>>> profile_version_2 = ProfileVersion(2, 1)
>>> profile_version_2 > profile_version_1
True
```

opencolorio_config_aces.SUPPORTED_PROFILE VERSIONS

```
opencolorio_config_aces.SUPPORTED_PROFILE VERSIONS = [ProfileVersion ('2.0'),
ProfileVersion ('2.1')]
```

Built-in mutable sequence.

If no argument is given, the constructor creates a new empty list. The argument must be an iterable if specified.

Config Generation Common Objects

opencolorio_config_aces

ConfigData(schema_version, profile_version, ...)	Define the data container for an <i>OpenColorIO</i> config.
deserialize_config_data(path)	Deserialize the <i>JSON OpenColorIO</i> config data container at given path.
generate_config(data[, config_name, ...])	Generate the <i>OpenColorIO</i> config from given data.
serialize_config_data(data, path)	Serialize the <i>OpenColorIO</i> config data container as a <i>JSON</i> file.
validate_config(config)	Validate given <i>OpenColorIO</i> config.

opencolorio_config_aces.ConfigData

```
class opencolorio_config_aces.ConfigData(schema_version: ~opencol-
                                             orio_config_aces.config.generation.profile_version.ProfileVersion
                                             = ProfileVersion ('1.0'), profile_version: ~opencol-
                                             orio_config_aces.config.generation.profile_version.ProfileVersion
                                             = ProfileVersion ('2.0'), name: str = <factory>,
                                             description: str = 'An "OpenColorIO" config generated by
                                             "OpenColorIO-Config-ACES".', search_path: list =
                                             <factory>, roles: dict = <factory>, colorspaces: list =
                                             <factory>, named_transforms: list = <factory>,
                                             view_transforms: list = <factory>, looks: list =
                                             <factory>, shared_views: list = <factory>, views: list =
                                             <factory>, active_displays: list = <factory>,
                                             active_views: list = <factory>, file_rules: list =
                                             <factory>, viewing_rules: list = <factory>,
                                             inactive_colorspaces: list = <factory>,
                                             default_view_transform: str = <factory>)
```

Define the data container for an *OpenColorIO* config.

Parameters

- **profile_version** ([ProfileVersion](#), optional) – Config major and minor version, i.e. (1, 0) or (2, 0).
- **name** (unicode, optional) – Config name.
- **description** (unicode, optional) – Config description.
- **search_path** ([list](#), optional) – Config search path.
- **roles** ([dict](#)) – Config roles, a dict of role and *Colorspace* name.
- **colorspaces** (array_like) – Config colorspaces, an iterable of `PyOpenColorIO.ColorSpace` class instances or mappings to create them with [opencolorio_config_aces.colorspace_factory\(\)](#) definition.
- **named_transforms** (array_like) – Config *NamedTransform*'s, an iterable of :attr:`PyOpenColorIO.NamedTransform` class instances or mappings to create them with [opencolorio_config_aces.named_transform_factory\(\)](#) definition.
- **view_transforms** (array_like, optional) – Config view transforms, an iterable of `PyOpenColorIO.ViewTransform` class instances or mappings to create them with [opencolorio_config_aces.view_transform_factory\(\)](#) definition.
- **looks** (array_like, optional) – Config looks, an iterable of `PyOpenColorIO.Look` class instances or mappings to create them with [opencolorio_config_aces.look_factory\(\)](#) definition.
- **shared_views** (array_like, optional) – Config shared views, an iterable of dicts of view, *ViewTransform*, *Colorspace* and rule names, iterable of looks and description.
- **views** (array_like, optional) – Config views, an iterable of dicts of display, view and *Colorspace* names.
- **active_displays** (array_like, optional) – Config active displays, an iterable of display names.
- **active_views** (array_like, optional) – Config active displays, an iterable of view names.
- **file_rules** (array_like, optional) – Config file rules, a dict of file rules.
- **viewing_rules** (array_like, optional) – Config viewing rules, a dict of viewing rules.
- **inactive_colorspaces** (array_like, optional) – Config inactive colorspaces, an iterable of *Colorspace* names.
- **default_view_transform** (unicode, optional) – Name of the default view transform.

schema_version

Type

[opencolorio_config_aces.config.generation.profile_version.ProfileVersion](#)

profile_version

Type

[opencolorio_config_aces.config.generation.profile_version.ProfileVersion](#)

name

Type

`str`

description

Type

str

search_path

Type

list

roles

Type

dict

colorspaces

Type

list

named_transforms

Type

list

view_transforms

Type

list

looks

Type

list

shared_views

Type

list

views

Type

list

active_displays

Type

list

active_views

Type

list

file_rules

Type

list

viewing_rules

Type

list

inactive_colorspaces

Type

list

default_view_transform

Type

str

__init__(schema_version: ~opencolorio_config_aces.config.generation.profile_version.ProfileVersion = ProfileVersion(1.0), profile_version: ~opencolorio_config_aces.config.generation.profile_version.ProfileVersion = ProfileVersion(2.0), name: str = <factory>, description: str = 'An "OpenColorIO" config generated by "OpenColorIO-Config-ACES".', search_path: list = <factory>, roles: dict = <factory>, colorspaces: list = <factory>, named_transforms: list = <factory>, view_transforms: list = <factory>, looks: list = <factory>, shared_views: list = <factory>, views: list = <factory>, active_displays: list = <factory>, active_views: list = <factory>, file_rules: list = <factory>, viewing_rules: list = <factory>, inactive_colorspaces: list = <factory>, default_view_transform: str = <factory>) → None

Methods

__init__([schema_version, profile_version, ...])

Attributes

description

profile_version

schema_version

name

search_path

roles

colorspaces

named_transforms

view_transforms

looks

shared_views

views

active_displays

active_views

file_rules

viewing_rules

inactive_colorspaces

default_view_transform

opencolorio_config_aces.deserialize_config_data

opencolorio_config_aces.**deserialize_config_data**(*path*)

Deserialize the JSON OpenColorIO config data container at given path.

Parameters

path (unicode) – JSON file path.

Returns

Deserialized JSON OpenColorIO config data container.

Return type

ConfigData

opencolorio_config_aces.generate_config

```
opencolorio_config_aces.generate_config(data, config_name=None, validate=True,  
                                         base_config=None)
```

Generate the *OpenColorIO* config from given data.

Parameters

- **data** (`ConfigData`) – *OpenColorIO* config data.
- **config_name** (unicode, optional) – *OpenColorIO* config file name, if given the config will be written to disk.
- **validate** (`bool`, optional) – Whether to validate the config.
- **base_config** (`bool`, optional) – *OpenColorIO* base config inherited for initial data.

Returns

OpenColorIO config.

Return type

`Config`

opencolorio_config_aces.serialize_config_data

```
opencolorio_config_aces.serialize_config_data(data, path)
```

Serialize the *OpenColorIO* config data container as a *JSON* file.

Parameters

- **data** (`ConfigData`) – *OpenColorIO* config data container to serialize.
- **path** (unicode) – *JSON* file path.

opencolorio_config_aces.validate_config

```
opencolorio_config_aces.validate_config(config)
```

Validate given *OpenColorIO* config.

Parameters

config (`Config`) – *OpenColorIO* config to validate.

Returns

Whether the *OpenColorIO* config is valid.

Return type

`bool`

Factories

opencolorio_config_aces

BUILTIN_TRANSFORMS	Mapping of <i>OpenColorIO</i> builtintransforms to their profile version.
TRANSFORM_FACTORIES	<i>OpenColorIO</i> transform factories.
colorspace_factory(name[, family, encoding, ...])	<i>OpenColorIO</i> Colorspace factory.
group_transform_factory(transforms)	<i>OpenColorIO</i> GroupTransform factory.
look_factory(name[, process_space, ...])	<i>OpenColorIO</i> Look factory.
named_transform_factory(name[, family, ...])	<i>OpenColorIO</i> NamedTransform factory.
produce_transform(transform)	Produce given transform.
transform_factory(**kwargs)	<i>OpenColorIO</i> transform factory.
view_transform_factory(name[, family, ...])	<i>OpenColorIO</i> ViewTransform factory.

opencolorio_config_aces.BUILTIN_TRANSFORMS

```
opencolorio_config_aces.BUILTIN_TRANSFORMS = {'ACES-LMT - ACES 1.3 Reference Gamut Compression': ProfileVersion ('2.1'), 'ACES-LMT - BLUE_LIGHT_ARTIFACT_FIX': ProfileVersion ('2.0'), 'ACES-OUTPUT - ACES2065-1_to_CIE-XYZ-D65 - HDR-CINEMA-108nit-7.2nit-P3lim_1.1': ProfileVersion ('2.0'), 'ACES-OUTPUT - ACES2065-1_to_CIE-XYZ-D65 - HDR-VIDEO-1000nit-15nit-P3lim_1.1': ProfileVersion ('2.0'), 'ACES-OUTPUT - ACES2065-1_to_CIE-XYZ-D65 - HDR-VIDEO-1000nit-15nit-REC2020lim_1.1': ProfileVersion ('2.0'), 'ACES-OUTPUT - ACES2065-1_to_CIE-XYZ-D65 - HDR-VIDEO-2000nit-15nit-P3lim_1.1': ProfileVersion ('2.0'), 'ACES-OUTPUT - ACES2065-1_to_CIE-XYZ-D65 - HDR-VIDEO-2000nit-15nit-REC2020lim_1.1': ProfileVersion ('2.0'), 'ACES-OUTPUT - ACES2065-1_to_CIE-XYZ-D65 - SDR-CINEMA-D60sim-D65_1.1': ProfileVersion ('2.0'), 'ACES-OUTPUT - ACES2065-1_to_CIE-XYZ-D65 - SDR-CINEMA-D60sim-DCI_1.0': ProfileVersion ('2.0'), 'ACES-OUTPUT - ACES2065-1_to_CIE-XYZ-D65 - SDR-CINEMA-D65sim-DCI_1.1': ProfileVersion ('2.0'), 'ACES-OUTPUT - ACES2065-1_to_CIE-XYZ-D65 - SDR-CINEMA-REC709lim_1.1': ProfileVersion ('2.0'), 'ACES-OUTPUT - ACES2065-1_to_CIE-XYZ-D65 - SDR-CINEMA_1.0': ProfileVersion ('2.0'), 'ACES-OUTPUT - ACES2065-1_to_CIE-XYZ-D65 - SDR-VIDEO-D60sim-D65_1.0': ProfileVersion ('2.0'), 'ACES-OUTPUT - ACES2065-1_to_CIE-XYZ-D65 - SDR-VIDEO-P3lim_1.1': ProfileVersion ('2.0'), 'ACES-OUTPUT - ACES2065-1_to_CIE-XYZ-D65 - SDR-VIDEO-REC709lim_1.1': ProfileVersion ('2.0'), 'ACES-OUTPUT - ACES2065-1_to_CIE-XYZ-D65 - SDR-VIDEO_1.0': ProfileVersion ('2.0'), 'ACEScc_to_ACES2065-1': ProfileVersion ('2.0'), 'ACEScct_to_ACES2065-1': ProfileVersion ('2.0'), 'ACEScg_to_ACES2065-1': ProfileVersion ('2.0'), 'ACESproxy10i_to_ACES2065-1': ProfileVersion ('2.0'), 'ADX10_to_ACES2065-1': ProfileVersion ('2.0'), 'ADX16_to_ACES2065-1': ProfileVersion ('2.0'), 'ARRI_ALEXA-LOGC-EI800-AWG_to_ACES2065-1': ProfileVersion ('2.0'), 'CANON_CLOG2-CGAMUT_to_ACES2065-1': ProfileVersion ('2.0'), 'CANON_CLOG3-CGAMUT_to_ACES2065-1': ProfileVersion ('2.0'), 'CURVE - ACEScct-LOG_to_LINEAR': ProfileVersion ('2.0'), 'CURVE - LINEAR_to_ST-2084': ProfileVersion ('2.0'), 'CURVE - ST-2084_to_LINEAR': ProfileVersion ('2.0'), 'DISPLAY - CIE-XYZ-D65_to_G2.2-REC.709': ProfileVersion ('2.0'), 'DISPLAY - CIE-XYZ-D65_to_G2.6-P3-D60-BFD': ProfileVersion ('2.0'), 'DISPLAY - CIE-XYZ-D65_to_G2.6-P3-D65': ProfileVersion ('2.0'), 'DISPLAY - CIE-XYZ-D65_to_G2.6-P3-DCI-BFD': ProfileVersion ('2.0'), 'DISPLAY - CIE-XYZ-D65_to_REC.1886-REC.2020': ProfileVersion ('2.0'), 'DISPLAY - CIE-XYZ-D65_to_REC.1886-REC.709': ProfileVersion ('2.0'), 'DISPLAY - CIE-XYZ-D65_to_REC.2100-HLG-1000nit': ProfileVersion ('2.0'), 'DISPLAY - CIE-XYZ-D65_to_REC.2100-PQ': ProfileVersion ('2.0'), 'DISPLAY - CIE-XYZ-D65_to_ST2084-P3-D65': ProfileVersion ('2.0'), 'DISPLAY - CIE-XYZ-D65_to_sRGB': ProfileVersion ('2.0'), 'IDENTITY': ProfileVersion ('2.0'), 'PANASONIC_VLOG-VGAMUT_to_ACES2065-1': ProfileVersion ('2.0'), 'RED_LOG3G10-RWG_to_ACES2065-1': ProfileVersion ('2.0'), 'RED_REDLOGFILM-RWG_to_ACES2065-1': ProfileVersion ('2.0'), 'SONY_SLOG3-SGAMUT3-VENICE_to_ACES2065-1': ProfileVersion ('2.0'), 'SONY_SLOG3-SGAMUT3.CINE-VENICE_to_ACES2065-1': ProfileVersion ('2.0'), 'SONY_SLOG3-SGAMUT3.CINE_to_ACES2065-1': ProfileVersion ('2.0'), 'SONY_SLOG3-SGAMUT3_to_ACES2065-1': ProfileVersion ('2.0'), 'UTILITY - ACES-AP0_to_CIE-XYZ-D65_BFD': ProfileVersion ('2.0'), 'UTILITY - ACES-AP1_to_CIE-XYZ-D65_BFD': ProfileVersion ('2.0'), 'UTILITY - ACES-AP1_to_LINEAR-REC709_BFD': ProfileVersion ('2.0')}
```

Mapping of *OpenColorIO* builtintransforms to their profile version.

BUILTIN_TRANSFORMS : dict

opencolorio_config_aces.TRANSFORM_FACTORIES

```
opencolorio_config_aces.TRANSFORM_FACTORIES = {'CLF Transform to Group Transform':  
<function transform_factory_clf_transform_to_group_transform>, 'Constructor': <function  
transform_factory_constructor>, 'Setter': <function transform_factory_setter>}
```

OpenColorIO transform factories.

TRANSFORM_FACTORIES : dict

opencolorio_config_aces.colorspace_factory

```
opencolorio_config_aces.colorspace_factory(name, family=None, encoding=None, aliases=None,  
categories=None, description=None,  
equality_group=None, bit_depth=None,  
allocation=None, allocation_vars=None,  
to_reference=None, from_reference=None,  
is_data=None, reference_space=None,  
base_colorspace=None, **kwargs)
```

OpenColorIO Colorspace factory.

Parameters

- **name** (unicode) – *OpenColorIO* Colorspace name.
- **family** (unicode, optional) – *OpenColorIO* Colorspace family.
- **encoding** (unicode, optional) – *OpenColorIO* Colorspace encoding.
- **aliases** (unicode or array_like, optional) – *OpenColorIO* Colorspace aliases.
- **categories** (unicode or array_like, optional) – *OpenColorIO* Colorspace categories.
- **description** (unicode, optional) – *OpenColorIO* Colorspace description.
- **equality_group** (unicode, optional) – *OpenColorIO* Colorspace equality_group.
- **bit_depth** (int, optional) – *OpenColorIO* Colorspace bit depth.
- **allocation** (int, optional) – *OpenColorIO* Colorspace allocation type.
- **allocation_vars** (tuple, optional) – *OpenColorIO* Colorspace allocation variables.
- **to_reference** (dict or object, optional) – *To Reference* *OpenColorIO* transform.
- **from_reference** (dict or object, optional) – *From Reference* *OpenColorIO* transform.
- **reference_space** (unicode or ReferenceSpaceType, optional) – *OpenColorIO* Colorspace reference space.
- **is_data** (bool, optional) – Whether the Colorspace represents data.
- **base_colorspace** (dict or ColorSpace, optional) – *OpenColorIO* base Colorspace inherited for initial attribute values.
- ****kwargs** (dict, optional) – Keywords arguments.

Returns

OpenColorIO colorspace.

Return type

ocio.ColorSpace

opencolorio_config_aces.group_transform_factory

`opencolorio_config_aces.group_transform_factory(transforms)`

OpenColorIO GroupTransform factory.

Parameters

`transforms` (array_like) – *OpenColorIO transforms.*

Returns

OpenColorIO GroupTransform.

Return type

`ocio.GroupTransform`

opencolorio_config_aces.look_factory

`opencolorio_config_aces.look_factory(name, process_space=None, description=None, forward_transform=None, inverse_transform=None, base_look=None, **kwargs)`

OpenColorIO Look factory.

Parameters

- `name` (unicode) – *OpenColorIO Look name.*
- `process_space` (unicode, optional) – *OpenColorIO Look process space, e.g. OpenColorIO Colorspace or role name.*
- `description` (unicode, optional) – *OpenColorIO Look description.*
- `forward_transform` (dict or object, optional) – *To Reference OpenColorIO Look transform.*
- `inverse_transform` (dict or object, optional) – *From Reference OpenColorIO Look transform.*
- `base_look` (dict or ViewTransform, optional) – *OpenColorIO base Look inherited for initial attribute values.*
- `**kwargs` (dict, optional) – *Keywords arguments.*

Returns

OpenColorIO Look.

Return type

`ocio.Look`

opencolorio_config_aces.named_transform_factory

`opencolorio_config_aces.named_transform_factory(name, family=None, encoding=None, aliases=None, categories=None, description=None, forward_transform=None, inverse_transform=None, base_named_transform=None, **kwargs)`

OpenColorIO NamedTransform factory.

Parameters

- `name` (unicode) – *OpenColorIO NamedTransform name.*
- `family` (unicode, optional) – *OpenColorIO NamedTransform family.*
- `encoding` (unicode, optional) – *OpenColorIO NamedTransform encoding.*

- **aliases** (unicode or array_like, optional) – *OpenColorIO NamedTransform* aliases.
- **categories** (unicode or array_like, optional) – *OpenColorIO NamedTransform* categories.
- **description** (unicode, optional) – *OpenColorIO NamedTransform* description.
- **forward_transform** (dict or object, optional) – Forward *OpenColorIO* transform.
- **inverse_transform** (dict or object, optional) – Inverse *OpenColorIO* transform.
- **base_named_transform** (dict or NamedTransform, optional) – *OpenColorIO* base *NamedTransform* inherited for initial attribute values.
- ****kwargs** (dict, optional) – Keywords arguments.

Returns

OpenColorIO NamedTransform.

Return type

ocio.NamedTransform

opencolorio_config_aces.produce_transform

opencolorio_config_aces.**produce_transform**(transform)

Produce given transform.

Parameters

transform (object or dict or array_like) – Transform to produce, either a single transform if a *Mapping* instance or a *GroupTransform* is a *Sequence* instance.

Returns

OpenColorIO transform.

Return type

object

opencolorio_config_aces.transform_factory

opencolorio_config_aces.**transform_factory**(**kwargs)

OpenColorIO transform factory.

Parameters

- **factory** (unicode) – {'Default', 'CLF Transform to GroupTransform'}, *OpenColorIO* transform factory name.
- ****kwargs** (dict, optional) – Keywords arguments for the factory.

Returns

OpenColorIO transform.

Return type

object

opencolorio_config_aces.view_transform_factory

```
opencolorio_config_aces.view_transform_factory(name, family=None, categories=None,
                                              description=None, to_reference=None,
                                              from_reference=None, reference_space=None,
                                              base_view_transform=None, **kwargs)
```

OpenColorIO ViewTransform factory.

Parameters

- **name** (unicode) – *OpenColorIO ViewTransform name.*
- **family** (unicode, optional) – *OpenColorIO ViewTransform family.*
- **categories** (array_like, optional) – *OpenColorIO ViewTransform categories.*
- **description** (unicode, optional) – *OpenColorIO ViewTransform description.*
- **to_reference** (dict or object, optional) – *To Reference OpenColorIO ViewTransform.*
- **from_reference** (dict or object, optional) – *From Reference OpenColorIO ViewTransform.*
- **reference_space** (unicode or ReferenceSpaceType, optional) – *OpenColorIO ViewTransform reference space.*
- **base_view_transform** (dict or ViewTransform, optional) – *OpenColorIO base ViewTransform inherited for initial attribute values.*
- ****kwargs** (dict, optional) – *Keywords arguments.*

Returns

OpenColorIO ViewTransform.

Return type

ocio.ViewTransform

Reference Configuration**aces-dev Discovery****opencolorio_config_aces**

<code>version_aces_dev()</code>	Return the current <i>aces-dev</i> version, trying first with <i>git</i> , then by parsing the <i>CHANGELOG.md</i> file.
<code>classify_aces_ctl_transforms(...)</code>	Classifie given ACES CTL transforms.
<code>discover_aces_ctl_transforms([root_directory])</code>	Discover the ACES CTL transform paths in given root directory: The given directory is traversed and the *.ctl files are collected.
<code>filter_aces_ctl_transforms(ctl_transforms[, ...])</code>	Filter given ACES CTL transforms with given filterers.
<code>print_aces_taxonomy()</code>	Print <i>aces-dev</i> taxonomy:
<code>unclassify_aces_ctl_transforms(...)</code>	Unclassifie given ACES CTL transforms.

opencolorio_config_aces.version_aces_dev

`opencolorio_config_aces.version_aces_dev()`

Return the current *aces-dev* version, trying first with *git*, then by parsing the *CHANGELOG.md* file.

Returns

aces-dev version.

Return type

`str`

opencolorio_config_aces.classify_aces_ctl_transforms

`opencolorio_config_aces.classify_aces_ctl_transforms(unclassified_ctl_transforms)`

Classifie given ACES CTL transforms.

Parameters

`unclassified_ctl_transforms` (`dict`) – Unclassified ACES CTL transforms as returned by `opencolorio_config_aces.discover_aces_ctl_transforms()` definition.

Returns

`{“family”1: {“genus”1: {}CTL1, …, “family”n: {“genus”2: {}CTL2}}`

where

`{}CTLn = {“basename”n: CTLTransformn, …, “basename”n+1: CTLTransformn+1}`

Return type

`dict`

Examples

```
>>> ctl_transforms = classify_aces_ctl_transforms(  
...     discover_aces_ctl_transforms())  
>>> family = sorted(ctl_transforms.keys())[0]  
>>> str(family)  
'csc'  
>>> genera = sorted(ctl_transforms[family])  
>>> print(genera)  
['ACEScc', 'ACEScct', 'ACEScg', 'ACESproxy', 'ADX', 'arri', 'canon', 'panasonic',  
 'red', 'sony']  
>>> genus = genera[0]  
>>> sorted(ctl_transforms[family][genus].items())  
[(ACEScsc.Academy.ACEScc', CTLTransformPair(CTLTransform('csc...ACEScc...ACEScsc.  
...Academy.ACES_to_ACEScc.ctl'), CTLTransform('csc...ACEScc...ACEScsc.Academy.ACEScc_  
...to_ACES.ctl')))]
```

opencolorio_config_aces.discover_aces_ctl_transforms

```
opencolorio_config_aces.discover_aces_ctl_transforms(root_directory='/home/docs/checkouts/readthedocs.org/user_
config-aces/envs/stable/lib/python3.9/site-
packages/opencolorio_config_aces/config/reference/aces-
dev/transforms/ctl')
```

Discover the ACES CTL transform paths in given root directory: The given directory is traversed and the *.ctl files are collected.

Parameters

root_directory (unicode) – Root directory to traverse to find the ACES CTL transforms.

Returns

```
{“directory”1: [“transforma.ctl”, “transformb.ctl”], 
..., 
“directory”n: [“transformc.ctl”, “transformd.ctl”]}
```

Return type

dict

Examples

```
>>> ctl_transforms = discover_aces_ctl_transforms()
>>> key = sorted(ctl_transforms.keys())[0]
>>> os.path.basename(key)
'ACEScc'
>>> sorted([os.path.basename(path) for path in ctl_transforms[key]])
['ACEScsc.Academy.ACES_to_ACEScc.ctl', 'ACEScsc.Academy.ACEScc_to_ACES.ctl']
```

opencolorio_config_aces.filter_ctl_transforms

```
opencolorio_config_aces.filter_ctl_transforms(ctl_transforms, filterers=None)
```

Filter given ACES CTL transforms with given filterers.

Parameters

- **ctl_transforms** (dict or list) – ACES CTL transforms as returned by `opencolorio_config_aces.classify_aces_ctl_transforms()` or `opencolorio_config_aces.unclassify_aces_ctl_transforms()` definitions.
- **filterers** (array_like, optional) – List of callables used to filter the ACES CTL transforms, each callable takes an ACES CTL transform as argument and returns whether to include or exclude the ACES CTL transform as a bool.

Returns

[$CTLTransform_1, \dots, CTLTransform_n$]

Return type

list

Warning:

- This definition will forcibly unclassify the given ACES CTL transforms and return a flattened list.

Examples

```
>>> ctl_transforms = classify_aces_ctl_transforms(  
...     discover_aces_ctl_transforms())  
>>> sorted(  
...     filter_ctl_transforms(ctl_transforms, [lambda x: x.genus == 'p3']),  
...     key=lambda x: x.path)[0]  
CTLTransform('odt...p3...Inv0DT.Academy.P3D60_48nits.ctl')
```

opencolorio_config_aces.print_aces_taxonomy

opencolorio_config_aces.**print_aces_taxonomy()**

Print *aces-dev* taxonomy:

- The *aces-dev* *CTL* transforms are discovered by traversing the directory defined by the `opencolorio_config_aces.config.reference.ROOT_TRANSFORMS_CTL` attribute using the `opencolorio_config_aces.discover_aces_ctl_transforms()` definition.
- The *CTL* transforms are classified by *family* e.g. *output_transform*, and *genus* e.g. *dcdm* using the `opencolorio_config_aces.classify_aces_ctl_transforms()` definition.
- The resulting data structure is printed.

opencolorio_config_aces.unclassify_ctl_transforms

opencolorio_config_aces.**unclassify_ctl_transforms(classified_ctl_transforms)**

Unclassifie given *ACES* *CTL* transforms.

Parameters

`classified_ctl_transforms (dict)` – Classified *ACES* *CTL* transforms as returned by `opencolorio_config_aces.classify_aces_ctl_transforms()` definition.

Returns

$[CTLTransform_1, \dots, CTLTransform_n]$

Return type

`list`

Examples

```
>>> ctl_transforms = classify_aces_ctl_transforms(  
...     discover_aces_ctl_transforms())  
>>> sorted(  
...     unclassify_ctl_transforms(ctl_transforms), key=lambda x: x.path)[0]  
CTLTransform('csc...ACEScc...ACEScsc.Academy.ACES_to_ACEScc.ctl')
```

***aces-dev* Conversion Graph**`opencolorio_config_aces`

<code>build_aces_conversion_graph(ctl_transforms)</code>	Build the <i>aces-dev</i> conversion graph from given <i>ACES CTL</i> transforms.
<code>conversion_path(graph, source, target)</code>	Return the conversion path from the source node to the target node in the <i>aces-dev</i> conversion graph.
<code>ctl_transform_to_node(graph, ctl_transform)</code>	Return the node name from given <i>ACES CTL</i> transform.
<code>filter_nodes(graph[, filterers])</code>	Filter given <i>aces-dev</i> conversion graph nodes with given filterers.
<code>node_to_ctl_transform(graph, node)</code>	Return the <i>ACES CTL</i> transform from given node name.
<code>plot_aces_conversion_graph(graph, filename)</code>	Plot given <i>aces-dev</i> conversion graph using Graphviz and pygraphviz .

`opencolorio_config_aces.build_aces_conversion_graph``opencolorio_config_aces.build_aces_conversion_graph(ctl_transforms)`Build the *aces-dev* conversion graph from given *ACES CTL* transforms.**Parameters**

`ctl_transforms` (dict or list) – *ACES CTL* transforms as returned by `opencolorio_config_aces.classify_aces_ctl_transforms()`, `opencolorio_config_aces.unclassify_aces_ctl_transforms()` or `opencolorio_config_aces.filter_ctl_transforms()` definitions.

Returns*aces-dev* conversion graph.**Return type**

DiGraph

Examples

```
>>> ctl_transforms = classify_aces_ctl_transforms(
...     discover_aces_ctl_transforms())
>>> build_aces_conversion_graph(ctl_transforms)
<networkx.classes.digraph.DiGraph object at 0x...>
```

`opencolorio_config_aces.conversion_path``opencolorio_config_aces.conversion_path(graph, source, target)`Return the conversion path from the source node to the target node in the *aces-dev* conversion graph.**Parameters**

- `graph` (DiGraph) – *aces-dev* conversion graph.
- `source` (unicode) – Source node.
- `target` (unicode) – Target node.

Returns

Conversion path from the source node to the target node.

Return type

list

Examples

```
>>> ctl_transforms = classify_aces_ctl_transforms(  
...     discover_aces_ctl_transforms())  
>>> graph = build_aces_conversion_graph(ctl_transforms)  
>>> conversion_path(graph, 'IDT/Venice_SLog3_SGamut3', 'ODT/P3D60_48nits')  
[('IDT/Venice_SLog3_SGamut3', 'ACES2065-1'), ('ACES2065-1', 'OCES'), ('OCES', 'ODT/  
→P3D60_48nits')]
```

opencolorio_config_aces.ctl_transform_to_node

opencolorio_config_aces.**ctl_transform_to_node**(graph, ctl_transform)

Return the node name from given ACES CTL transform.

Parameters

- **graph** (DiGraph) – aces-dev conversion graph.
- **ctl_transform** (CTLTransform) – ACES CTL transform to return the node name from.

Returns

Node name.

Return type

unicode

Examples

```
>>> ctl_transforms = classify_aces_ctl_transforms(  
...     discover_aces_ctl_transforms())  
>>> graph = build_aces_conversion_graph(ctl_transforms)  
>>> ctl_transform = node_to_ctl_transform(graph, 'ODT/P3D60_48nits')  
>>> ctl_transform_to_node(graph, ctl_transform)  
'ODT/P3D60_48nits'
```

opencolorio_config_aces.filter_nodes

opencolorio_config_aces.**filter_nodes**(graph, filterers=None)

Filter given aces-dev conversion graph nodes with given filterers.

Parameters

- **graph** (DiGraph) – aces-dev conversion graph.
- **filterers** (array_like, optional) – List of callables used to filter the ACES CTL transforms, each callable takes an ACES CTL transform as argument and returns whether to include or exclude the ACES CTL transform as a bool.

Returns

Filtered aces-dev conversion graph nodes.

Return type
list

Examples

```
>>> ctl_transforms = classify_aces_ctl_transforms(
...     discover_aces_ctl_transforms())
>>> graph = build_aces_conversion_graph(ctl_transforms)
>>> sorted(filter_nodes(graph, [lambda x: x.genus == 'p3']))[0]
'InvRRTODT/P3D65_1000nits_15nits_ST2084'
```

opencolorio_config_aces.node_to_ctl_transform

opencolorio_config_aces.**node_to_ctl_transform**(*graph, node*)

Return the ACES CTL transform from given node name.

Parameters

- **graph** (DiGraph) – *aces-dev* conversion graph.
- **node** (unicode) – Node name to return the ACES CTL transform from.

Returns

ACES CTL transform.

Return type

CTLTransform

Examples

```
>>> ctl_transforms = classify_aces_ctl_transforms(
...     discover_aces_ctl_transforms())
>>> graph = build_aces_conversion_graph(ctl_transforms)
>>> node_to_ctl_transform(graph, 'ODT/P3D60_48nits')
CTLTransform('odt...p3...ODT.Academy.P3D60_48nits.ctl')
```

opencolorio_config_aces.plot_aces_conversion_graph

opencolorio_config_aces.**plot_aces_conversion_graph**(*graph, filename, prog='dot', args=''*)

Plot given *aces-dev* conversion graph using [Graphviz](#) and [pygraphviz](#).

Parameters

- **graph** (DiGraph) – *aces-dev* conversion graph.
- **filename** (unicode) – Filename to use to save the image.
- **prog** (unicode, optional) – {'neato', 'dot', 'twopi', 'circo', 'fdp', 'nop'}, *Graphviz* layout method.
- **args** (unicode, optional) – Additional arguments for *Graphviz*.

Returns

PyGraphviz graph.

Return type

AGraph

aces-dev Reference Config Generator

`opencolorio_config_aces`

<code>ColorspaceDescriptionStyle(value)</code>	Enum storing the various <i>OpenColorIO Colorspace</i> description styles.
<code>version_config_mapping_file([path])</code>	Return the current version of given CSV mapping file.
<code>generate_config_aces([config_name, ...])</code>	Generate the <i>aces-dev</i> reference implementation <i>OpenColorIO</i> config using the <i>Mapping</i> method.

`opencolorio_config_aces.ColorspaceDescriptionStyle`

`class opencolorio_config_aces.ColorspaceDescriptionStyle(value)`

Enum storing the various *OpenColorIO Colorspace* description styles.

`__init__()`

Attributes

NONE

ACES

OPENCOLORIO

SHORT

LONG

SHORT_UNION

LONG_UNION

`opencolorio_config_aces.version_config_mapping_file`

`opencolorio_config_aces.version_config_mapping_file(path=PosixPath('/home/docs/checkouts/readthedocs.org/user_`
`config-aces/envs/stable/lib/python3.9/site-`
`packages/opencolorio_config_aces/config/reference/generate/`
`Config-ACES Reference Transforms - v1.0.0 -`
`Reference Config - Mapping.csv'))`

Return the current version of given CSV mapping file.

No parsing of the file content is perform, a simple regex is used to extract the version of the file name.

Parameters

`path` (Path or `str`, optional) – Path to the CSV mapping file.

Returns

CSV mapping file version.

Return type

`str`

Examples

```
>>> path = (
...     "/tmp/OpenColorIO-Config-ACES Reference Transforms - v0.1.0 - "
...     "Reference Config - Mapping.csv"
... )
>>> version_config_mapping_file(path)
'v0.1.0'
>>> path = (
...     "/tmp/OpenColorIO-Config-ACES Reference Transforms - "
...     "Reference Config - Mapping.csv"
... )
>>> version_config_mapping_file(path)
''
```

`opencolorio_config_aces.generate_config_aces`

```
opencolorio_config_aces.generate_config_aces(config_name=None,
                                              profile_version=ProfileVersion('2.0'), validate=True,
                                              describe=ColorspaceDescriptionStyle.SHORT_UNION,
                                              config_mapping_file_path=PosixPath('/home/docs/checkouts/readthedocs-
                                              config-aces/envs/stable/lib/python3.9/site-
                                              packages/opencolorio_config_aces/config/reference/generate/resources/
                                              Config-ACES Reference Transforms - v1.0.0 -
                                              Reference Config - Mapping.csv'), analytical=True,
                                              scheme='Modern 1', additional_data=False)
```

Generate the *aces-dev* reference implementation *OpenColorIO* config using the *Mapping* method.

The config generation is constrained by a CSV file exported from the *Reference Config - Mapping* sheet from a [Google Sheets file](#). The *Google Sheets* file was originally authored using the output of the *aces-dev* conversion graph to support the discussions of the *OpenColorIO Working Group* on the design of the *aces-dev* reference implementation *OpenColorIO* config. The resulting mapping is the outcome of those discussions and leverages the new *OpenColorIO 2* display architecture while factoring many transforms.

Parameters

- **config_name** (`unicode`, optional) – *OpenColorIO* config file name, if given the config will be written to disk.
- **profile_version** (`ProfileVersion`, optional) – *OpenColorIO* config profile version.
- **validate** (`bool`, optional) – Whether to validate the config.
- **describe** (`int`, optional) – Any value from the `opencolorio_config_aces.ColorspaceDescriptionStyle` enum.
- **config_mapping_file_path** (`unicode`, optional) – Path to the CSV mapping file used by the *Mapping* method.
- **analytical** (`bool`, optional) – Whether to generate *OpenColorIO* transform families that analytically match the given ACES CTL transform, i.e. true to the *aces-dev* reference but not necessarily user friendly.
- **scheme** (`str`, optional) – {"Legacy", "Modern 1"}, Naming convention scheme to use.
- **additional_data** (`bool`, optional) – Whether to return additional data.

Returns

OpenColorIO config or tuple of *OpenColorIO* config and `opencolorio_config_aces.ConfigData` class instance.

Return type

Config or tuple

ACES Computer Graphics (CG) Config Generator

`opencolorio_config_aces`

<code>generate_config_cg([data, config_name, ...])</code>	Generate the ACES Computer Graphics (CG) <i>OpenColorIO</i> config.
---	---

`opencolorio_config_aces.generate_config_cg`

```
opencolorio_config_aces.generate_config_cg(data=None, config_name=None,
                                              profile_version=ProfileVersion('2.0'), validate=True,
                                              describe=ColorspaceDescriptionStyle.SHORT_UNION,
                                              config_mapping_file_path=PosixPath('/home/docs/checkouts/readthedoc-
                                              config-aces/envs/stable/lib/python3.9/site-
                                              packages/opencolorio_config_aces/config/cg/generate/resources/OpenCol-
                                              Config-ACES CG and Studio Transforms - v1.0.0 - CG
                                              Config - Mapping.csv'), scheme='Modern 1',
                                              additional_data=False)
```

Generate the ACES Computer Graphics (CG) *OpenColorIO* config.

The default process is as follows:

- The ACES CG *OpenColorIO* config generator invokes the *aces-dev* reference implementation *OpenColorIO* config generator via the `opencolorio_config_aces.generate_config_aces()` definition and the default reference config mapping file.
- The ACES CG *OpenColorIO* config generator filters and extends the data from the *aces-dev* reference implementation *OpenColorIO* config with the given CG config mapping file:
 - The builtin *CLF* transforms are discovered and classified.
 - The CG config mapping file is parsed.
 - The list of implicit colorspace is built, e.g. *ACES2065-1*, *Raw*, etc...
 - The colorspace, looks and view transforms are filtered according to the parsed CG config mapping file data.
 - The displays, views, and shared views are filtered similarly.
 - The active displays and views are also filtered.
 - The builtin *CLF* transforms are filtered according to the parsed CG config mapping file data and converted to colorspace (or named transforms).
 - Finally, the roles and aliases are updated.

Parameters

- `data` (`ConfigData`, optional) – *OpenColorIO* config data to derive the config from, the default is to use the *aces-dev* reference implementation *OpenColorIO* config.
- `config_name` (unicode, optional) – *OpenColorIO* config file name, if given the config will be written to disk.

- **profile_version** (`ProfileVersion`, optional) – *OpenColorIO* config profile version.
- **validate** (`bool`, optional) – Whether to validate the config.
- **describe** (`int`, optional) – Any value from the `opencolorio_config_aces.ColorspaceDescriptionStyle` enum.
- **config_mapping_file_path** (`unicode`, optional) – Path to the *CSV* mapping file used to describe the transforms mapping.
- **scheme** (`str`, optional) – {“Legacy”, “Modern 1”}, Naming convention scheme to use.
- **additional_data** (`bool`, optional) – Whether to return additional data.

Returns

OpenColorIO config or tuple of *OpenColorIO* config and `opencolorio_config_aces.ConfigData` class instance.

Return type

Config or `tuple`

ACES Studio Config Generator

`opencolorio_config_aces`

```
generate_config_studio([data, config_name, Generate the ACES Studio OpenColorIO config.
...])
```

`opencolorio_config_aces.generate_config_studio`

```
opencolorio_config_aces.generate_config_studio(data=None, config_name=None,
                                                profile_version=ProfileVersion('2.0'),
                                                validate=True, de-
                                                scribe=ColorspaceDescriptionStyle.SHORT_UNION,
                                                config_mapping_file_path=PosixPath('/home/docs/checkouts/readth-
                                                config-aces/envs/stable/lib/python3.9/site-
                                                packages/opencolorio_config_aces/config/studio/generate/resources/
                                                Config-ACES CG and Studio Transforms - v1.0.0 -
                                                Studio Config - Mapping.csv'), scheme='Modern 1',
                                                additional_data=False)
```

Generate the ACES Studio *OpenColorIO* config.

The default process is as follows:

- The ACES Studio *OpenColorIO* config generator invokes the ACES CG *OpenColorIO* config generator with the given studio config mapping file via the `opencolorio_config_aces.generate_config_cg()` definition.
- The ACES CG *OpenColorIO* config generator invokes the *aces-dev* reference implementation *OpenColorIO* config generator via the `opencolorio_config_aces.generate_config_aces()` definition and the default reference config mapping file.
- With the data from the *aces-dev* reference implementation *OpenColorIO* config generated, the ACES CG *OpenColorIO* config generator produces the ACES Studio *OpenColorIO* config by filtering and extending it with the given studio config mapping file.

Parameters

- **data** (`ConfigData`, optional) – *OpenColorIO* config data to derive the config from, the default is to use the *ACES CG OpenColorIO* config.
- **config_name** (unicode, optional) – *OpenColorIO* config file name, if given the config will be written to disk.
- **profile_version** (`ProfileVersion`, optional) – *OpenColorIO* config profile version.
- **validate** (`bool`, optional) – Whether to validate the config.
- **describe** (`int`, optional) – Any value from the `opencolorio_config_aces.ColorspaceDescriptionStyle` enum.
- **config_mapping_file_path** (unicode, optional) – Path to the CSV mapping file used to describe the transforms mapping.
- **scheme** (`str`, optional) – {"Legacy", "Modern 1"}, Naming convention scheme to use.
- **additional_data** (`bool`, optional) – Whether to return additional data.

Returns

OpenColorIO config or tuple of *OpenColorIO* config and `opencolorio_config_aces.ConfigData` class instance.

Return type

Config or `tuple`

Utilities

Common

`opencolorio_config_aces.utilities`

<code>ROOT_BUILD_DEFAULT</code>	Path subclass for non-Windows systems.
<code>DocstringDict</code>	A <code>dict</code> sub-class that allows settings a docstring to <code>dict</code> instances.
<code>first_item(iterable[, default])</code>	Return the first item of given iterable.
<code>common_ancestor(*args)</code>	Return the common ancestor of given iterables.
<code>paths_common_ancestor(*args)</code>	Return the common ancestor path from given paths.
<code>vivification()</code>	Implement supports for vivification of the underlying dict like data-structure, magical!
<code>vivified_to_dict(vivified)</code>	Convert given vivified data-structure to dictionary.
<code>message_box(message[, width, padding, ...])</code>	Print a message inside a box.
<code>is_colour_installed([raise_exception])</code>	Return if <i>Colour</i> is installed and available.
<code>is_jsonpickle_installed([raise_exception])</code>	Return if <i>jsonpickle</i> is installed and available.
<code>is_networkx_installed([raise_exception])</code>	Return if <i>NetworkX</i> is installed and available.
<code>REQUIREMENTS_TO_CALLABLE</code>	Mapping of requirements to their respective callables.
<code>required(*requirements)</code>	Decorate a function to check whether various ancillary package requirements are satisfied.
<code>is_string(a)</code>	Return if given <i>a</i> variable is a <i>string</i> like variable.
<code>is_iterable(a)</code>	Return if given <i>a</i> variable is iterable.
<code>git_describe()</code>	Describe the current <i>OpenColorIO Configuration for ACES</i> git version.
<code>matrix_3x3_to_4x4(M)</code>	Convert given 3x3 matrix <i>M</i> to a raveled 4x4 matrix.
<code>multi_replace(name, patterns)</code>	Update given name by applying in succession the given patterns and substitutions.
<code>regularise_version(version[, add_v_prefix])</code>	Regularise given version name by either adding or removing a <i>v</i> affixe.
<code>validate_method(method, valid_methods[, message])</code>	Validate whether given method exists in the given valid methods and returns the method lower cased.
<code>google_sheet_title(url)</code>	Return the title from given <i>Google Sheet</i> url.
<code>slugify(object_[, allow_unicode])</code>	Generate a <i>SEO</i> friendly and human-readable slug from given object.

opencolorio_config_aces.utilities.ROOT_BUILD_DEFAULT

```
opencolorio_config_aces.utilities.ROOT_BUILD_DEFAULT =
PosixPath('/home/docs/checkouts/readthedocs.org/user_builds/opencolorio-config-aces/envs/
stable/lib/python3.9/site-packages/build')
```

Path subclass for non-Windows systems.

On a POSIX system, instantiating a Path should return this object.

opencolorio_config_aces.utilities.DocstringDict

```
class opencolorio_config_aces.utilities.DocstringDict
```

A `dict` sub-class that allows settings a docstring to `dict` instances.

```
__init__(*args, **kwargs)
```

Methods

```
__init__(*args, **kwargs)
```

```
clear()
```

```
copy()
```

<code>fromkeys([value])</code>	Create a new dictionary with keys from iterable and values set to value.
--------------------------------	--

<code>get(key[, default])</code>	Return the value for key if key is in the dictionary, else default.
----------------------------------	---

```
items()
```

```
keys()
```

<code>pop(k[,d])</code>	If key is not found, default is returned if given, otherwise <code>KeyError</code> is raised
-------------------------	--

<code>popitem()</code>	Remove and return a (key, value) pair as a 2-tuple.
------------------------	---

<code>setdefault(key[, default])</code>	Insert key with a value of default if key is not in the dictionary.
---	---

<code>update([E,]**F)</code>	If E is present and has a <code>.keys()</code> method, then does: for k in E: <code>D[k] = E[k]</code> If E is present and lacks a <code>.keys()</code> method, then does: for k, v in E: <code>D[k] = v</code> In either case, this is followed by: for k in F: <code>D[k] = F[k]</code>
-------------------------------	---

```
values()
```

opencolorio_config_aces.utilities.first_item

```
opencolorio_config_aces.utilities.first_item(iterable, default=None)
```

Return the first item of given iterable.

Parameters

- `iterable` (`iterable`) – Iterable
- `default` (`object`) – Default value if the iterable is empty.

Returns

First iterable item.

Return type

`object`

opencolorio_config_aces.utilities.common_ancestor

```
opencolorio_config_aces.utilities.common_ancestor(*args)
```

Return the common ancestor of given iterables.

Parameters

***args** (`list`, optional) – Iterables to retrieve the common ancestor from.

Returns

Common ancestor.

Return type

iterable

Examples

```
>>> common_ancestor(['1', '2', '3'), ('1', '2', '0'), ('1', '2', '3', '4'))
('1', '2')
>>> common_ancestor('azerty', 'azetty', 'azello')
'aze'
```

opencolorio_config_aces.utilities.paths_common_ancestor

```
opencolorio_config_aces.utilities.paths_common_ancestor(*args)
```

Return the common ancestor path from given paths.

Parameters

***args** (`list`, optional) – Paths to retrieve common ancestor from.

Returns

Common path ancestor.

Return type

unicode

Examples

```
>>> paths_common_ancestor(
...     '/Users/JohnDoe/Documents', '/Users/JohnDoe/Documents/Test.txt')
'/Users/JohnDoe/Documents'
```

opencolorio_config_aces.utilities.vivification

```
opencolorio_config_aces.utilities.vivification()
```

Implement supports for vivification of the underlying dict like data-structure, magical!

Return type

defaultdict

Examples

```
>>> vivified = vivification()
>>> vivified['my']['attribute'] = 1
>>> vivified['my']
defaultdict(<function vivification at 0x...>, {u'attribute': 1})
>>> vivified['my']['attribute']
1
```

opencolorio_config_aces.utilities.vivified_to_dict

opencolorio_config_aces.utilities.**vivified_to_dict**(vivified)

Convert given vivified data-structure to dictionary.

Parameters

vivified (defaultdict) – Vivified data-structure.

Return type

dict

Examples

```
>>> vivified = vivification()
>>> vivified['my']['attribute'] = 1
>>> vivified_to_dict(vivified)
{u'my': {u'attribute': 1}}
```

opencolorio_config_aces.utilities.message_box

opencolorio_config_aces.utilities.**message_box**(message, width=79, padding=3,
print_callable=<built-in function print>)

Print a message inside a box.

Parameters

- **message** (unicode) – Message to print.
- **width** (int, optional) – Message box width.
- **padding** (unicode, optional) – Padding on each sides of the message.
- **print_callable** (callable, optional) – Callable used to print the message box.

Returns

Definition success.

Return type

bool

Examples

```
>>> message = ('Lorem ipsum dolor sit amet, consectetur adipiscing elit, '
...     'sed do eiusmod tempor incididunt ut labore et dolore magna '
...     'aliqua.')
>>> message_box(message, width=75)
=====
*                               *
*   Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do   *
*   eiusmod tempor incididunt ut labore et dolore magna aliqua.       *
*                               *
=====
True
>>> message_box(message, width=60)
=====
*                               *
*   Lorem ipsum dolor sit amet, consectetur adipiscing   *
*   elit, sed do eiusmod tempor incididunt ut labore et   *
*   dolore magna aliqua.           *
*                               *
=====
True
>>> message_box(message, width=75, padding=16)
=====
*                               *
*           Lorem ipsum dolor sit amet, consectetur   *
*           adipiscing elit, sed do eiusmod tempor   *
*           incididunt ut labore et dolore magna   *
*           aliqua.           *
*                               *
=====
True
```

`opencolorio_config_aces.utilities.is_colour_installed`

`opencolorio_config_aces.utilities.is_colour_installed(raise_exception=False)`

Return if *Colour* is installed and available.

Parameters

`raise_exception` (`bool`) – Raise exception if *Colour* is unavailable.

Returns

Is *Colour* installed.

Return type

`bool`

Raises

`ImportError` – If *Colour* is not installed.

`opencolorio_config_aces.utilities.is_jsonpickle_installed`

`opencolorio_config_aces.utilities.is_jsonpickle_installed(raise_exception=False)`

Return if `jsonpickle` is installed and available.

Parameters

`raise_exception (bool)` – Raise exception if `jsonpickle` is unavailable.

Returns

Is `jsonpickle` installed.

Return type

`bool`

Raises

`ImportError` – If `jsonpickle` is not installed.

`opencolorio_config_aces.utilities.is_networkx_installed`

`opencolorio_config_aces.utilities.is_networkx_installed(raise_exception=False)`

Return if `NetworkX` is installed and available.

Parameters

`raise_exception (bool)` – Raise exception if `NetworkX` is unavailable.

Returns

Is `NetworkX` installed.

Return type

`bool`

Raises

`ImportError` – If `NetworkX` is not installed.

`opencolorio_config_aces.utilities.REQUIREMENTS_TO_CALLABLE`

`opencolorio_config_aces.utilities.REQUIREMENTS_TO_CALLABLE = {'Colour': <function is_colour_installed>, 'NetworkX': <function is_networkx_installed>, 'jsonpickle': <function is_jsonpickle_installed>}`

Mapping of requirements to their respective callables.

`_REQUIREMENTS_TO_CALLABLE`

[CaseInsensitiveMapping] {‘Colour’, ‘jsonpickle’, ‘NetworkX’, ‘OpenImageIO’}

`opencolorio_config_aces.utilities.required`

`opencolorio_config_aces.utilities.required(*requirements)`

Decorate a function to check whether various ancillary package requirements are satisfied.

Parameters

`*requirements (list, optional)` – Requirements to check whether they are satisfied.

Return type

`object`

opencolorio_config_aces.utilities.is_string

```
opencolorio_config_aces.utilities.is_string(a)
```

Return if given *a* variable is a *string* like variable.

Parameters

a (`object`) – Data to test.

Returns

Is *a* variable a *string* like variable.

Return type

`bool`

Examples

```
>>> is_string("I'm a string!")
True
>>> is_string(["I'm a string!"])
False
```

opencolorio_config_aces.utilities.is_iterable

```
opencolorio_config_aces.utilities.is_iterable(a)
```

Return if given *a* variable is iterable.

Parameters

a (`object`) – Variable to check the iterability.

Returns

a variable iterability.

Return type

`bool`

Examples

```
>>> is_iterable([1, 2, 3])
True
>>> is_iterable(1)
False
```

opencolorio_config_aces.utilities.git_describe

```
opencolorio_config_aces.utilities.git_describe()
```

Describe the current *OpenColorIO Configuration for ACES* git version.

Returns

- `>>> git_describe() # doctest (+SKIP)`
- `'0.1.0'`

`opencolorio_config_aces.utilities.matrix_3x3_to_4x4`

`opencolorio_config_aces.utilities.matrix_3x3_to_4x4(M)`

Convert given 3x3 matrix M to a raveled 4x4 matrix.

Parameters

`M` (`array_like`) – 3x3 matrix M to convert.

Returns

Raveled 4x4 matrix.

Return type

`list`

`opencolorio_config_aces.utilities.multi_replace`

`opencolorio_config_aces.utilities.multi_replace(name, patterns)`

Update given name by applying in succession the given patterns and substitutions.

Parameters

- `name` (`unicode`) – Name to update.
- `patterns` (`dict`) – Dictionary of regular expression patterns and substitution to apply onto the name.

Returns

Updated name.

Return type

`unicode`

Examples

```
>>> multi_replace(  
...     'Canon Luke Skywalker was weak and powerless.',  
...     {'Canon': 'Legends', 'weak': 'strong', '\w+less': 'powerful'})  
'Legends Luke Skywalker was strong and powerful.'
```

`opencolorio_config_aces.utilities.regularise_version`

`opencolorio_config_aces.utilities.regularise_version(version, add_v_prefix=True)`

Regularise given version name by either adding or removing a `v` affixe.

Parameters

- `version` (`str`) – Version name to regularise.
- `add_v_prefix` (`bool`, optional) – Whether to add the `v` affixe.

Returns

Regularise version name.

Return type

`str`

Examples

```
>>> regularise_version("0.1.0")
'v0.1.0'
>>> regularise_version("v0.1.0")
'v0.1.0'
>>> regularise_version("v0.1.0", False)
'0.1.0'
>>> regularise_version("0.1.0", False)
'0.1.0'
```

opencolorio_config_aces.utilities.validate_method

`opencolorio_config_aces.utilities.validate_method(method, valid_methods, message="{}
method is invalid, it must be one of {}!")`

Validate whether given method exists in the given valid methods and returns the method lower cased.

Parameters

- **method** (`str`) – Method to validate.
- **valid_methods** (`Union[Sequence, Mapping]`) – Valid methods.
- **message** (`str`) – Message for the exception.

Returns

Method lower cased.

Return type

`str`

Raises

`ValueError` – If the method does not exist.

Examples

```
>>> validate_method('Valid', ['Valid', 'Yes', 'Ok'])
'valid'
```

opencolorio_config_aces.utilities.google_sheet_title

`opencolorio_config_aces.utilities.google_sheet_title(url)`

Return the title from given *Google Sheet* url.

Parameters

`url` (`str`) – *Google Sheet* url to return the title of.

Returns

Google Sheet title.

Return type

`str`

Examples

```
>>> url = (
...     "https://docs.google.com/spreadsheets/d/"
...     "1SXPt-USy3H1V2G2qAvh9zit6ZCIND0lfKT07yXJdWLg/"
...     "export?format=csv&gid=273921464"
... )
>>> google_sheet_title(url)
'OpenColorIO-Config-ACES "Reference" Transforms - v...'
```

opencolorio_config_aces.utilities.slugify

opencolorio_config_aces.utilities.**slugify**(*object*, *allow_unicode=False*)

Generate a *SEO* friendly and human-readable slug from given object.

Convert to ASCII if *allow_unicode* is *False*. Convert spaces or repeated dashes to single dashes. Remove characters that aren't alphanumerics, underscores, or hyphens. Convert to lowercase. Also strip leading and trailing whitespace, dashes, and underscores.

Parameters

- **object** (`object`) – Object to convert to a slug.
- **allow_unicode** (`bool`) – Whether to allow unicode characters in the generated slug.

Returns

Generated slug.

Return type

`str`

References

- <https://github.com/django/django/blob/0dd29209091280ccf34e07c9468746c396b7778e/django/utils/text.py#L400>

Examples

```
>>> slugify(
...     " Jack & Jill like numbers 1,2,3 and 4 and silly characters ?%.$!/"
... )
'jack-jill-like-numbers-123-and-4-and-silly-characters'
```

3.1.2 Indices and tables

- genindex
- search

CHAPTER
FOUR

1.4 ABOUT

OpenColorIO Configuration for ACES by OpenColorIO Contributors
Copyright Contributors to the OpenColorIO Project – ocio-dev@lists.aswf.io
This software is released under terms of New BSD License:
<https://opensource.org/licenses/BSD-3-Clause>
<https://github.com/AcademySoftwareFoundation/OpenColorIO-Config-ACES>

INDEX

Symbols

`--init__()` (*opencolorio_config_aces.ColorspaceDescriptionStyle method*), 38
`--init__()` (*opencolorio_config_aces.ConfigData method*), 23
`--init__()` (*opencolorio_config_aces.ProfileVersion method*), 19
`--init__()` (*opencolorio_config_aces.utilities.DocstringDict method*), 44
orio_config_aces.ConfigData attribute, 23
description (opencolorio_config_aces.ConfigData attribute), 21
deserialize_config_data() (in module opencolorio_config_aces), 24
discover_aces_ctl_transforms() (in module opencolorio_config_aces), 33
discover_clf_transforms() (in module opencolorio_config_aces), 12
DocstringDict (class in opencolorio_config_aces.utilities), 44

A

`active_displays` (*opencolorio_config_aces.ConfigData attribute*), 22
`active_views` (*opencolorio_config_aces.ConfigData attribute*), 22

B

`build_aces_conversion_graph() (in module opencolorio_config_aces)`, 35
`BUILTIN_TRANSFORMS (in module opencolorio_config_aces)`, 26

C

`classify_aces_ctl_transforms() (in module opencolorio_config_aces)`, 32
`classify_clf_transforms() (in module opencolorio_config_aces)`, 11
`colorspace_factory() (in module opencolorio_config_aces)`, 28
`ColorspaceDescriptionStyle (class in opencolorio_config_aces)`, 38
`colorspaces (opencolorio_config_aces.ConfigData attribute)`, 22
`common_ancestor() (in module opencolorio_config_aces.utilities)`, 45
`ConfigData (class in opencolorio_config_aces)`, 20
`conversion_path() (in module opencolorio_config_aces)`, 35
`ctl_transform_to_node() (in module opencolorio_config_aces)`, 36

D

`default_view_transform` (*opencolorio*

orio_config_aces.ConfigData attribute), 23
description (opencolorio_config_aces.ConfigData attribute), 21
deserialize_config_data() (in module opencolorio_config_aces), 24
discover_aces_ctl_transforms() (in module opencolorio_config_aces), 33
discover_clf_transforms() (in module opencolorio_config_aces), 12
DocstringDict (class in opencolorio_config_aces.utilities), 44

F

`file_rules (opencolorio_config_aces.ConfigData attribute)`, 22
`filter_clf_transforms() (in module opencolorio_config_aces)`, 13
`filter_ctl_transforms() (in module opencolorio_config_aces)`, 33
`filter_nodes() (in module opencolorio_config_aces)`, 36
`first_item() (in module opencolorio_config_aces.utilities)`, 44

G

`generate_clf_transform() (in module opencolorio_config_aces)`, 14
`generate_clf_transforms_arri() (in module opencolorio_config_aces.clf)`, 15
`generate_clf_transforms_bmdfilm() (in module opencolorio_config_aces.clf)`, 15
`generate_clf_transforms_canon() (in module opencolorio_config_aces.clf)`, 16
`generate_clf_transforms_davinci() (in module opencolorio_config_aces.clf)`, 16
`generate_clf_transforms_itu() (in module opencolorio_config_aces.clf)`, 17
`generate_clf_transforms_ocio() (in module opencolorio_config_aces.clf)`, 17
`generate_clf_transforms_panasonic() (in module opencolorio_config_aces.clf)`, 17
`generate_clf_transforms_red() (in module opencolorio_config_aces.clf)`, 17
`generate_clf_transforms_sony() (in module opencolorio_config_aces.clf)`, 18

generate_config() (in module <code>opencolorio_config_aces</code>), 25	opencolorio_config_aces	node_to_ctl_transform() (in module <code>opencolorio_config_aces</code>), 37
generate_config_aces() (in module <code>opencolorio_config_aces</code>), 39	opencolorio_config_aces	
generate_config_cg() (in module <code>opencolorio_config_aces</code>), 40	opencolorio_config_aces	
generate_config_studio() (in module <code>opencolorio_config_aces</code>), 41	opencolorio_config_aces	
git_describe() (in module <code>opencolorio_config_aces.utilities</code>), 49	opencolorio_config_aces.utilities	
google_sheet_title() (in module <code>opencolorio_config_aces.utilities</code>), 51	opencolorio_config_aces.utilities	
group_transform_factory() (in module <code>opencolorio_config_aces</code>), 29	opencolorio_config_aces	
I		
inactive_colorspaces (opencolorio_config_aces.ConfigData attribute), 22	opencolorio_config_aces.ConfigData	
is_colour_installed() (in module <code>opencolorio_config_aces.utilities</code>), 47	opencolorio_config_aces.utilities	
is_iterable() (in module <code>opencolorio_config_aces.utilities</code>), 49	opencolorio_config_aces.utilities	
is_jsonpickle_installed() (in module <code>opencolorio_config_aces.utilities</code>), 48	opencolorio_config_aces.utilities	
is_networkx_installed() (in module <code>opencolorio_config_aces.utilities</code>), 48	opencolorio_config_aces.utilities	
is_string() (in module <code>opencolorio_config_aces.utilities</code>), 49	opencolorio_config_aces.utilities	
L		
look_factory() (in module <code>opencolorio_config_aces</code>), 29	opencolorio_config_aces	
looks (opencolorio_config_aces.ConfigData attribute), 22	opencolorio_config_aces.ConfigData	
M		
major (in module <code>opencolorio_config_aces</code>), 19	opencolorio_config_aces	
major (opencolorio_config_aces.ProfileVersion attribute), 18	opencolorio_config_aces.ProfileVersion	
matrix_3x3_to_4x4() (in module <code>opencolorio_config_aces.utilities</code>), 50	opencolorio_config_aces.utilities	
message_box() (in module <code>opencolorio_config_aces.utilities</code>), 46	opencolorio_config_aces.utilities	
minor (in module <code>opencolorio_config_aces</code>), 19	opencolorio_config_aces	
minor (opencolorio_config_aces.ProfileVersion attribute), 18	opencolorio_config_aces.ProfileVersion	
multi_replace() (in module <code>opencolorio_config_aces.utilities</code>), 50	opencolorio_config_aces.utilities	
N		
name (opencolorio_config_aces.ConfigData attribute), 21	opencolorio_config_aces.ConfigData	
named_transform_factory() (in module <code>opencolorio_config_aces</code>), 29	opencolorio_config_aces	
named_transforms (opencolorio_config_aces.ConfigData attribute), 22	opencolorio_config_aces.ConfigData	
P		
paths_common_ancestor() (in module <code>opencolorio_config_aces.utilities</code>), 45	opencolorio_config_aces.utilities	
plot_aces_conversion_graph() (in module <code>opencolorio_config_aces</code>), 37	opencolorio_config_aces	
print_aces_taxonomy() (in module <code>opencolorio_config_aces</code>), 34	opencolorio_config_aces	
print_clf_taxonomy() (in module <code>opencolorio_config_aces</code>), 13	opencolorio_config_aces	
produce_transform() (in module <code>opencolorio_config_aces</code>), 30	opencolorio_config_aces	
profile_version (opencolorio_config_aces.ConfigData attribute), 21	opencolorio_config_aces.ConfigData	
PROFILE_VERSION_DEFAULT (in module <code>opencolorio_config_aces</code>), 19	opencolorio_config_aces	
ProfileVersion (class in <code>opencolorio_config_aces</code>), 18	opencolorio_config_aces	
R		
regularise_version() (in module <code>opencolorio_config_aces.utilities</code>), 50	opencolorio_config_aces.utilities	
required() (in module <code>opencolorio_config_aces.utilities</code>), 48	opencolorio_config_aces.utilities	
REQUIREMENTS_TO_CALLABLE (in module <code>opencolorio_config_aces.utilities</code>), 48	opencolorio_config_aces.utilities	
roles (opencolorio_config_aces.ConfigData attribute), 22	opencolorio_config_aces.ConfigData	
ROOT_BUILD_DEFAULT (in module <code>opencolorio_config_aces.utilities</code>), 43	opencolorio_config_aces.utilities	
S		
schema_version (opencolorio_config_aces.ConfigData attribute), 21	opencolorio_config_aces.ConfigData	
search_path (opencolorio_config_aces.ConfigData attribute), 22	opencolorio_config_aces.ConfigData	
serialize_config_data() (in module <code>opencolorio_config_aces</code>), 25	opencolorio_config_aces	
shared_views (opencolorio_config_aces.ConfigData attribute), 22	opencolorio_config_aces.ConfigData	
slugify() (in module <code>opencolorio_config_aces.utilities</code>), 52	opencolorio_config_aces.utilities	
SUPPORTED_PROFILE VERSIONS (in module <code>opencolorio_config_aces</code>), 20	opencolorio_config_aces	
T		
TRANSFORM_FACTORIES (in module <code>opencolorio_config_aces</code>), 28	opencolorio_config_aces	
transform_factory() (in module <code>opencolorio_config_aces</code>), 30	opencolorio_config_aces	
U		
unclassify_clf_transforms() (in module <code>opencolorio_config_aces</code>), 14	opencolorio_config_aces	

unclassify_ctl_transforms() (*in module opencolorio_config_aces*), 34

V

validate_config() (*in module opencolorio_config_aces*), 25

validate_method() (*in module opencolorio_config_aces.utilities*), 51

version_aces_dev() (*in module opencolorio_config_aces*), 32

version_config_mapping_file() (*in module opencolorio_config_aces*), 38

view_transform_factory() (*in module opencolorio_config_aces*), 31

view_transforms (*opencolorio_config_aces.ConfigData attribute*), 22

viewing_rules (*opencolorio_config_aces.ConfigData attribute*), 22

views (*opencolorio_config_aces.ConfigData attribute*), 22

vivification() (*in module opencolorio_config_aces.utilities*), 45

vivified_to_dict() (*in module opencolorio_config_aces.utilities*), 46